



Aluminium oxide primarily used for the production of aluminium — Determination of boron content — Curcumin spectrophotometric method

TECHNICAL CORRIGENDUM 1

Oxyde d'aluminium principalement utilisé pour la production de l'aluminium — Dosage du bore — Méthode spectrophotométrique à la curcumine

RECTIFICATIF TECHNIQUE 1

Technical corrigendum 1 to International Standard ISO 2865: 1973 was prepared by Technical Committee ISO/TC 47, *Chemistry*, Sub-Committee SC 7, *Aluminium oxide, cryolite, aluminium fluoride, sodium fluoride, carbonaceous products for the aluminium industry*.

Page 1

Clause 2

Replace the reference to ISO/R 802 by a reference to ISO 802: 1976.

Add the following reference:

"ISO 2927: 1973, Aluminium oxide used primarily for the production of aluminium — Sampling."

Page 2

Subclause 6.1

Replace the text of subclause 6.1 by the following text:

"Weigh, to the nearest 0,001 g, 1 g of the laboratory sample, dried at 300 °C, prepared as described in ISO 2927 and ISO 802 : 1976, subclause 3.3."

Pour plus d'infos, merci de nous contacter.

Association Sénégalaise de Normalisation

4 Avenue Jean Jaurès, Immeuble El Hadj Omar DIA, 6 ème Etage
Dakar - SENEGAL

Tel: +221 33 829 58 25

Email: asn@asn.sn